

Spec sheet

LINE: MEAT GRINDERS

MODEL: M-22R-1 & M-22R-2

PICTURE:



USE

- * Supermarkets
- * Butcher shops
- * Restaurants
- * etc.

CAPACITY AND DIMENSIONS				
MODEL	*MOTOR	**GRINDING CAPACITY (3/8) FIRST GROUND	**GRINDING CAPACITY (1/8) SECOND GROUND	
M-22R-1	1 HP/ 0.74 kw	9.60 kg/min	5.50 kg/min	
	single phase	21 lb/min	12 lb/min	
M-22R-2	2 HP/ 1.492 kw	9.75 kg/min	5.85 kg/min	
	single phase	21.46 lb/min	12.87 lb/min	

^{*}Motor available 110volts/60 Hz or 220 Volts/50 Hz optional ** 35° F / 2° C Fresh Meat, lab conditions

BENEFITS

- * High capacity head
- * Stainless steel construction
- * Deep pan
- * Powerful 1 HP (M-22 R) or 2 HP (M-22 R2) motor
- * Easy to clean

LINE: MEAT GRINDERS

MODEL: M-22R-1 & M-22R-2

BENEFITS



MINIMUM MAINTENANCE

Powerful oil bathed steel gears transmission, with no belts or pulleys to maintain



HYGIENIC

High grade stainless steel cabinet and tray, very resistant and easy to clean allowing a hygienic operation and a professional presentation

SPECIFICATIONS

MODEL	M-22R-1	M-22R-2
*Motor	1 HP/ 0.74 kw single phase	2 HP/ 1.492 kw single phase
Volts	110 volts	220 volts
**Grinding capacity (3/8) First Ground	9.60 kg/min 21 lb/min	9.75 kg/min 21.46 lb/min
**Grinding capacity (1/8) Second Ground	5.50 kg/min 12 lb/min	5.85 kg/min 12.87 lb/min
Leveling feet	Yes	Yes
Net weight	57 kg/125.5 lb	60 kg/132 lb
Shipping weight	71 kg/156 lb	74 kg/163 lb

^{*}Motor available 110volts/60 Hz or 220 Volts/50 Hz optional

LONG LASTING LIFE

The powerful oil bathed steel gears transmission (with no belts or pulleys to maintain) guarantees a long lasting life, with minimum noise and low maintenance cost.



Its high bigger grinding

SAVES TIME AND MONEY

Its high capacity head holds bigger pieces in to the grinding system, avoiding down time in cutting into smaller pieces.

LARGE CAPACITY AND SAFETY OPERATION

The M-22R is equipped with a safety protector guard in the feeding area avoiding accidents. However the stomper must always be used.





EASY TO CLEAN

Its practical grinding system and the feed pan can be completely disassembled in a few minutes without tools reducing time spent on cleaning and maintenance operations.

Grinding system components are strong cast iron parts, with dip tin plating for hygiene and corrosion resistance.



Includes Knife, 3/16 plate and stomper





Conforms Conforms
UL std 763 NSF-8



CONFORMS CAN/CSA STD C22.2



* Available only in equipment ordered under this spec



^{**} 35° F / 2° C Fresh Meat, lab conditions